## HYBRID PEROVSKITE/POLYMER MATERIAL. PREPARATION AND PHYSICOCHEMICAL PROPERTIES

<u>Nick Samuel Țolea</u><sup>1</sup>, Adina Căta<sup>1</sup>, Antonina Lazăr<sup>1</sup>, Ioana M.C. Ienașcu<sup>1,2</sup>, Paula Svera<sup>1</sup>, Daniel Ursu<sup>1</sup>, Corina Orha<sup>1</sup>, Anamaria Dabici<sup>1</sup>, Paula Sfîrloagă<sup>1,3</sup>

 <sup>1</sup>National Institute of Research and Development for Electrochemistry and Condensed Matter, Dr. A. P. Podeanu 144, 300569, Timişoara, Romania
<sup>2</sup> "Vasile Goldiş" Western University of Arad, Faculty of Pharmacy, Liviu Rebreanu 86, 310045, Arad, Romania
<sup>3</sup>Spin-off Nattive-Senz SRL, Dr. A.P. Podeanu 144, 300569, Timisoara, Timis, Romania
e-mail: samy\_nick2008@yahoo.com

## Abstract

Organic–inorganic hybrid perovskites are a promising class of processable semiconducting materials that combine the favorable properties of the inorganic semiconductor with the flexibility and low-temperature processability of the organic material [1].

Here, we report on the synthesis and investigation of the properties of a novel polymerperovskite nanoparticles system based on LaMnO<sub>3</sub>:Ag nanocrystals protected by sodium polyacrylate polymer. The mixture of LaMnO<sub>3</sub>:Ag and sodium polyacrylate (1:20, m/m) were wet-triturated for 30 minutes, using water, until hydrogels were obtained. The resulting hydrogels were dried at 60 °C for 12 h and then mortared until obtaining a powder with particle dimensions up to 1 mm. Finally, the powder was subjected to another drying stage at 60 °C for 4 h.

The hybrid material was investigated by various characterization techniques, i.e. SEM/EDAX, X-ray diffraction, UV-VIS, FT-IR, and RAMAN spectroscopy. The obtained results confirm the formation of a novel polymer-perovskite nanoparticles system whose electrical and optical properties will be studied later.

## References

[1] G.C. Papavassiliou, G.A. Mousdis, I. Koutselas, in: T.-C. Sum, N. Mathews (Eds)., Halide Perovskites: Photovoltaics, Light Emitting Devices, and Beyond, Wiley-VCH GmbH & Co.: Hoboken, NJ, USA, 2019.

## Acknowledgements

This work was supported by the Experimental Demonstrative Project 683PED/2022.